

a measurable difference...



Carpet Dynamic Load Tester

Model: D0009

This instrument is used for determining the thickness loss of textile floor coverings under dynamic load. The specimen is subjected to a cyclic-loading treatment in which an impact assembly, with two feet on its underside, repeatedly droops freely onto the specimen. At the same time the specimen is slowly traversed. The thickness of the specimen is measured before and after the procedure.

Applications:

- All types of textile floor covering with a surface that is level in height and construction. It is not applicable to other floor coverings unless the areas of different thicknesses or construction can be tested separately.

Features:

- Bench-top operation
- Safety Enclosure
- Counter
- Totaliser



Standards:

- AS/NZS 2111.2:1996

Options:

- Not Applicable

Connections:

- **Electrical:** 220/240 VAC @ 50 HZ or 110 VAC @ 60 HZ

(please specify when ordering)

Dimensions:

- **H:** 390mm • **W:** 780mm • **D:** 540mm
- **Weight:** 60kg

10-11 Colrado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885

Fax: +61 3 9708 6770

Website: www.idminstruments.com.au

Email: idm@idminstruments.com.au

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments Pty Ltd[®] reserves the right to make alterations to its product range from time to time.