

*a measurable difference...*



## Coefficient of Linear Thermal Expansion Tester

### Model: C0007

This instrument is used for determining the linear change of a refractory caused by a change in temperature and to ascertain the reversibility of these characteristics.

It may also be used to determine the expansion and contraction characteristics of raw materials and refractories that do not exhibit reversible linear changes with increasing temperature.

### Applications:

- Manufacturing materials
- Acrylonitrile-Butadiene-Styrene (ABS)
- High Density Polyethylene (HDPE)
- Polyacetal (Acetal) POM
- Polyamide (Nylon) PA
- Polycarbonate (PC)
- Polyethylene (PE)
- Polyether-Ether-Ketone (PEEK)
- Polyethylene Terephthalate (PET)
- Polytetrafluoroethylene (PTFE)
- Other Plastics

### Features:

- Upper and Lower Limit Markers
- Easy-to-read dial gauge
- Bench-top operation

### Standards:

- ASTM D696

### Options:

- Digital

### Connections:

- **Electrical:** 220/240 VAC @ 50 HZ or 110 VAC @ 60 HZ

*(please specify when ordering)*

### Dimensions:

- **H:** 750mm
- **W:** 125mm
- **D:** 125mm
- **Weight:** 5kg



10-11 Colrado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885 Fax: +61 3 9708 6770

Website: [www.idminstruments.com.au](http://www.idminstruments.com.au) Email: [ids@idminstruments.com.au](mailto:ids@idminstruments.com.au)

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments Pty Ltd<sup>®</sup> reserves the right to make alterations to its product range from time to time.

Copyright © 2006 IDM Instruments Pty Ltd<sup>®</sup>. All Rights Reserved.