

*a measurable difference...*



## Concora Fluter

### Model: C0013

This machine is used to form test flutes in medium in preparation for crush tests. The temperature is maintained at a constant 175°C.

One roller is motor driven at 4 r/min, while the other is free to rotate with a minimum of friction or other resistance.

### Applications:

- Paper

### Features:

- Heated rollers
- Over-temperature alarm / cut out
- Industrial self-tuning temperature controllers
- Temperature accuracy: +/- 2°C
- Nip Load: 98 +/- 4N

### Standards:

- AS / NZ 1301.434
- CPPA D24
- DIN 53143
- SCAN P27
- ISO 7263
- TAPPI T-809
- TAPPI T824

### Options:

- Sample Holder

### Connections:

- **Electrical:** 220/240 VAC @ 50 HZ or 110 VAC @ 60 HZ

*(please specify when ordering)*

### Dimensions:

- **H:** 400mm    • **W:** 745mm    • **D:** 427mm
- **Weight:** 60kg



10-11 Colrado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885    Fax: +61 3 9708 6770

Website: [www.idminstruments.com.au](http://www.idminstruments.com.au)    Email: [idm@idminstruments.com.au](mailto:idm@idminstruments.com.au)

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments Pty Ltd<sup>®</sup> reserves the right to make alterations to its product range from time to time.

Copyright © 2006 IDM Instruments Pty Ltd<sup>®</sup>. All Rights Reserved.