

*a measurable difference...*



## Crease Bend Tester

### Model: B0012

The Crease Bend Tester is used to monitor scoring equipment to ensure box performance, by measuring the bending resistance of creased board at the time of folding at the crease. It measures the maximum force required to bend the sample board. Corrugated converters use the Crease Bend Tester to aid in making adjustments to improve the quality; thus ensuring the end user will have boxes that run effectively on their production line.

### Application:

- Board
- Corrugated Board

### Features:

- Range of 0 – 10,000 x 1gf
- Maximum Sample Width: 300mm
- Digital display
- Accuracy 1% FS
- Pneumatic sample clamp
- Motorised Load Bar
- Adjustable folding distance
- Peak Memory function
- Easy to operate
- Quick and simple testing

### Standards:

- N/A

### Options:

- RS 232

### Connections:

- **Air:** 80 psi Maximum
- **Electrical:** 220/240 VAC @ 50 HZ or  
110 VAC @ 60 HZ

*(please specify when ordering)*

### Dimensions:

- **H:** 360 mm
- **W:** 400 mm
- **D:** 350 mm
- **Weight:** 25 kg



10-11 Colrado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885 Fax: +61 3 9708 6770

Website: [www.idminstruments.com.au](http://www.idminstruments.com.au) Email: [ids@idminstruments.com.au](mailto:ids@idminstruments.com.au)

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments Pty Ltd<sup>®</sup> reserves the right to make alterations to its product range from time to time.

Copyright © 2006 IDM Instruments Pty Ltd<sup>®</sup>. All Rights Reserved.