

a measurable difference...



Flammability Tester

Model: F0009

This apparatus has been made to fill the standard requirements to test the combustion propagation characteristics of plastics, but not to assess fire hazards. It is used to measure flame duration and material consumed for small specimens of cellular plastics of densities less than 100kg/m, exposed to a small flame with the specimen in a vertical orientation.

Applications:

- Polystyrenes
- Polyisocyanurates
- Rigid polyurethane
- Flexible polyurethane

Features:

- Galvanised steel test chimney.
- "Analite" burner with ceramic orifices
- Remote ignition control
- Gas flow control unit

Standards:

- AS 2122.1

Options:

- Not Applicable

Connections:

- **Electrical:** 220/240 VAC @ 50 HZ or
110 VAC @ 60 HZ

(please specify when ordering)

Dimensions:

- **H:** 300mm • **W:** 400mm • **D:** 200mm
- **Weight:** 20kg



10-11 Colrado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885

Fax: +61 3 9708 6770

Website: www.idminstruments.com.au

Email: idm@idminstruments.com.au

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments Pty Ltd[®] reserves the right to make alterations to its product range from time to time.

Copyright © 2006 IDM Instruments Pty Ltd[®]. All Rights Reserved.