

a measurable difference...



Mooney Viscometer

Model: M0007

The Shearing Disc Viscometer, when applied to rubber or other elastomeric materials, is used as a standard method of determining the viscosity of such materials in the raw or compounded state, and for determining the curing characteristics of vulcanisable compounds.

Application:

- Rubber Compounds
- Cork Compounds
- Some Plastic Compounds

Features:

- Die closes pneumatically
- High to low pressure timer
- Zero reset for signal
- Test Run Timer

Standards:

- ASTM D1646

Options:

- N/A

Connections:

- **Electrical:** 220/240 VAC @ 50 HZ or
110 VAC @ 60 HZ

(please specify when ordering)

Dimensions:

- **H:** 1,800mm • **W:** 560mm • **D:** 560mm
- **Weight:** 165kg



10-11 Colrado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885 Fax: +61 3 9708 6770

Website: www.idminstruments.com.au Email: ids@idminstruments.com.au

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments Pty Ltd[®] reserves the right to make alterations to its product range from time to time.

Copyright © 2006 IDM Instruments Pty Ltd[®]. All Rights Reserved.