

a measurable difference...



Steel Cord Gas Tightness Tester

Model: SPM – SCG

The Steel Cord Gas Tightness Tester has been specially designed and manufactured with relevance to AS 1333 test standards.

It is used to determine the cord elastomeric compound penetration and actual condition of the steel-cord coating and penetration with core rubber and the corrosion protection of the steel-cords embedded in a conveyor belt.

Application:

- Rubber

Features:

- Digital Readout
- Clamping Device with handle
- Clamping Die
- Air Filter

Standards:

- AS 1333

Options:

- N/A

Connections:

- **Air:** 100 kPa
- **Electrical:** 220/240 VAC @ 50 HZ or
110 VAC @ 60 HZ

(please specify when ordering)

Dimensions:

- **H:** 200 mm • **W:** 555 mm • **D:** 402 mm
- **Weight:** 45 kg



10-11 Colrado Court, Hallam, Victoria 3803 Australia.

Phone: +61 3 9708 6885

Fax: +61 3 9708 6770

Website: www.idminstruments.com.au

Email: ids@idminstruments.com.au

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows. Products and details shown may change without notice as IDM Instruments Pty Ltd[®] reserves the right to make alterations to its product range from time to time.

Copyright © 2006 IDM Instruments Pty Ltd[®]. All Rights Reserved.